

Figure 1

2/6




Figure 2




Figure 3

3/6




Figure 4




Figure 5

4/6




Figure 6

BEST AVAILABLE COPY

5/6




Figure 7

Ref. Index	Transm.Wavelength		Material	Ref. Index at 250 nm
	$\lambda_o=250 \text{ nm}$			
-	$\phi = 20$	$\phi = 10$	-	
1.0	234.92	246.20	Sapphire	1.845
1.5	243.41	248.32	Quartz	1.600
2.0	246.32	249.06	CaF2	1.467
2.5	247.65	249.40		
5.0	249.41	249.85		

Figure 8

Fabry-Perot-Based Wavelength Modulation for Gas Sensing									
Gas Band Ctr.		Line Width		v/ Δv		FP-Spac.		Band Ctr.	
-	cm-1	$\Delta\lambda$ in cm-1	$\Delta\lambda$ in nm	ppm	mm	μm	nm	nm	nm
02	13145	2.121	0.174	161	2.357	0.380373	760.746	0.1228	12.2
02	13145	50.000	25.000	3804	0.100	0.380373	760.746	2.8937	2.0
02	13090	7.229	0.174	552	0.692	0.381971	760.942	0.4219	20.7
CO	2170	3.57	0.357	1645	1.401	2.304147	4608.295	7.5814	10.0
NO	30000	15000	250	500000	0.00033	0.166667	333.33	222.22	666.67
NO	33333	10000	278	300003	0.00050	0.150002	300.00	230.77	428.58
								166.67	NDIR absorption
								90.00	UV emissive
									UV emissive

Figure 9




Figure 10